







Broadcaster 4K AI

P/N: BRC-412/B



Laia Broadcaster 4K AI offers excellent performance and broad compatibility thanks to its multiple and comprehensive connection interfaces and control protocols. The real-time tracking of the speaker by artificial intelligence as well as its ISP processing technology and algorithms or its X12 optical zoom, make our camera the best solution for your conferences in medium and large rooms. In addition, the impressive 4K UHD image offered by its 1/2.8" CMOS sensor at up to 30fps together with its autofocus technology.

Main characteristics

 <p>HDMI Video Output - 3G-SDI - USB3.0 - IP</p>	 <p>AI Tracking</p>	 <p>4K quality</p>	 <p>Multiple protocols</p>	<p>NDI HX SRT</p> <p>Licensed NDI HX2 and SRT (Output up to 4KP30)</p>
---	--	---	---	--



* myTeam Sharer: Compatible solo video * Click Share Barco: Compatible solo video

4K AI Broadcaster Specifications: P/N: BRC-412/B

General

Sensor: High quality 1/28" CMOS

Pixel: 8.3M (3840x2160)

Video signal: HDMI: 4KP30, 4KP25, 1080P60, 1080P50, 1080P30, 1080P25, 720P60, 720P50, 1080P59.94, 1080P29.97, 720P59.94, 720P29.97; "P" refers to progressive scan. "i" refers to interlaced images. 3G-SDI: 1080P60, 1080P50, 1080P30, 1080P25, 720P60, 720P50, 1080P59.94, 1080P29.97, 720P59.94, 720P29.97; USB3.0: YUY2/NV12:1 920x1080P30, 1280x720P30, 1024x576P30, 800x600P30, 800x448P30, 640x360P30, 480x270P30, 320x180P30; MJPEG / H.26 / H.265 MJPEG / H.265: 3840x2160P30, 2560x1440P, 1920x1080P30, 1600x896P30, 1280x720P30, 1024x576P30, 960x540P30, 800x600P30, 800x448P30, 720x576P30, 720x480P30, 640x360P30, 640x480P30, 480x270, 320x240P30, 352x288P30, 320x176P30. USB3.0 Compatible with USB2.0: YUY2/NV12 supports 1920x1080P30, 1280x720P 25, 1024x576P30, 800x600P30, 800x448P30, 640x360P30, 480x270P30, 320x180P30; MJPEG/H.26H .265 supports 3840x2160P30, 2560x1440P, 1920x1080P30, 1600x896P30, 1280x720P30, 1024x576P30, 960x540P30, 800x600P30, 800x448P30, 720x576P30, 720x480P30, 640x360P30, 640x480P30, 480x270, 320x240P30, 352x288P30, 320x176P30

Optical zoom: 12X

Angle: Horizontal: 6.5° (N) ~ 70.9° (W).

Iris aperture: F1.8 ~ F2.8±5%.

Digital zoom: X15

Minimum illumination: 0.5Lux(F1.8, AGC switched on).

DNR: 2D&3D

White balance: Auto / Manual / One-push / Specific color temperature

Focus mode: Auto / Manual / One-push

Iris: F1.8 ~ F11, closed

Shutter speed: 1/25 ~ 1/20000

Dynamic range: Off, 1 ~ 8

Video adjustment: Brightness, hue, saturation, contrast, sharpness, black and white mode, gamma curve.

SNR: >50dB

Rear panel

Interface: HDMI, 3G-SDI, LAN(PoE), USB3.0 (Compatible with USB 2.0), A-IN, RS232-IN, RS232-OUT, RS422 (Compatible with RS485), DC12V power supply.

Output / video format: HDMI, 3G-SDI, LAN, USB3.0 (Compatible with USB 2.0) / LAN: H.264, H.265 | USB 3.0: MJPG, H264, YUY2, NV12

Audio input / output: Dual channel 3.5 mm linear input / HDMI, 3G-SDI, LAN, USB3.0. (Compatible with USB 2.0) MC, MP3, G.711A.

Network port: 10M/100M/1000M Ethernet port, PoE power, audio and video output.

Network protocol: RTSP, RTMP, ONVIF, GB/T28181, VISCA OVER IP, IP VISCA, RTMPS, SRT, remote update, reboot and reset.

Control interface: RS232-IN, RS232-OUT, RS422 compatible with RS485.

Protocol com port: VISCA/Pelco-D/Pelco-P; Baud rate: 115200/38400/9600/4800/2400

Power supply: HEC3800 Power Adapter (DC12V) Input: AC110V~AC220V ; Output: DC12V/2.5A

Voltaje / consumo: DC12V±10% / <12W

PTZ parameters

Tilt / swivel: -170° ~ +170° / -30° ~ +90°

Vel. tilt / rotation: 0.1°/s ~ 35°/s // 0.1°/s ~ 30°/s

Preset speed: Rotation: 35°/s, Tilt: 30°/s

Preset quantity: Up to 255 (10 in remote control)

Other parameters

Storage / use temp: -10°C ~ +70°C / -10°C ~ +50°C.

Hum. storage / use: 20% ~ 95% / 20% ~ 80%

Dimensions: 143(L)mm*176mm(W)*169mm(H)

Weight: 1.3 Kg



Central offices:
Av. Cerro del Águila, 3, 1B2.
S.S. de los Reyes 28703
Madrid - Spain

After-sales service:
C/Brújula, 4 Pol. Ind. PISA
Mairena del Aljarafe 41927
Seville - Spain