



The CM4 is a small 4" low impedance ceiling mount speaker. It is so stylish and discrete that it fits into any interior style or decoration, private or public. This speaker is small but offers good musical and speech quality.

The acoustical metal back can improve the sound response and protects against falling debris. This design makes CM4 speaker ideal for use in strip metal or perforated tile ceilings. Those ceilings allow the air that displaced by the loudspeaker cone to escape, resulting in a sound that lacks 'body'. The back can of CM4 prevents this and guarantees a full, rich sound.

Thanks to the strong spring clamps, the CM4 can be used in very thin ceiling material. It has only 100 mm mounting depth, which guarantees it can be used in a wide variety of applications.

CM4 can be used with a maximum of 4 speakers in parallel on one 4-Ohm amplifier channel. In situations where you want to give more punch to the music you can use the CM4 in combination with a CMSUB8 ceiling mount subwoofer or SUBTILE cabinet subwoofer.

The standard colour is white RAL 9010. From 12 pieces on, the loudspeakers can be painted optionally in any other RAL colour. (REF.:PAINTCMM)

TECHNICAL SPECIFICATIONS

Type:	CM4
Woofers:	4 inch, dual cone coated paper
Shape:	round
Rated power:	RMS 15W / 16Ohm
Music power:	RMS 30W / 16Ohm
Frequency response:	100Hz to 20kHz +-3dB
Dispersion:	at 1kHz, 4kHz, 8kHz 180°, 80°, 40°
Color:	White
Chassis type:	Full metal chassis
Grill construction:	Metal
IP class	60
Protected against falling debris:	yes, by backside can
Fixing type:	2 high strength springs
Cut out dimension:	115mm
Outside dimension:	135mm
Depth dimension:	100mm
Max wire size diameter:	2,5mm ²
Net weight:	0,785Kg
Gross weight:	0,925Kg

TENDER TEXT

The CM4 is a small round 4" low impedance ceiling mount speaker. It is equipped with a back can that protects the speaker from falling debris, and is ideal for use in strip metal or perforated tile ceilings. Those ceilings allow the air that displaced by the loudspeaker cone to escape, resulting in a sound that lacks 'body'. The back can of CM4 prevents this and guarantees a full, rich sound.

Thanks to the strong spring clamps, the CM4 can be used in very thin ceiling material. It has only 100 mm mounting depth, which guarantees it can be used in a wide variety of applications. CM4 has a full metal chassis and a metal grill. The speaker is a 4" dual cone treated woofer. The speaker is IP50 rated. It is possible to use a maximum of 4 speakers in parallel on one 4-Ohm amplifier channel.