

COLORdash™ Par-Hex 12



Powered by twelve hex-color RGBAW+UV LEDs, the ultra-compact COLORdash™ Par-Hex 12 satisfies the need for bright ultraviolet light without a separate UV fixture. The 12 LEDs project deeply saturated colors, any variation of white, and bold UV, all without multicolored shadows. A split-yoke bracket eliminates the need for floor stands. Power linking with a locking Neutrik® powerCON® power in and out, 3- and 5-pin DMX connectors make the fixture a great addition for tours, broadcast, and live production.

FEATURES

- Intensely bright LED PAR wash fixture for a wide array of lighting applications
- 12 hex-color (RGBAW+UV) LED chips for ultimate color mixing
- Simple and complex DMX channel profiles for programming versatility
- Four distinct dimming modes for easy incandescent replacement
- Lightweight for easy installation
- Silent, flicker-free operation
- Neutrik® powerCON® power input/output connections

SPECIFICATIONS

- DMX Channels: 3, 6, 8, 12 or 13
- Data Connectors: 3- and 5-pin XLR
- Light Source: 12 LEDs (hex-color RGBAW+UV)
10 W, (2.3 A), 50,000 hours life expectancy
- Built-in Automated Programs: Yes
- Customizable Programs: No
- Recall Custom Programs: No
- Accessory Holder/
Gel Frame Size: 9.5 in (241 mm)
- Shutter/Strobe: Electronic
- Strobe Rate: 0 to 20 Hz
- Standalone Color Mixing: Yes
- Color Temperature Presets: No
- Installed Optics: 25°
- Beam Angle: 20°
- Field Angle: 30°
- Dimming Modes: 4
- Illuminance: 927 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 17 units @ 120 V; 27 units @ 208 V; 30 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 96 W, 0.80 A @ 120 V, 60 Hz
- Power and Current: 95 W, 0.49 A @ 208 V, 60 Hz
- Power and Current: 95 W, 0.44 A @ 230 V, 50 Hz
- Weight: 10 lb (4.54 kg)
- Dimensions: 4.41 x 11.73 x 12.72 in (112 x 298 x 323 mm)
- Approvals: CE, MET