




Cute UP 4K Pro

P/N: CUP

Thanks to its features, Cute UP 4K Pro turns any meeting room into a collaboration room with the best quality -4K at 30 fps- to be used with any video conferencing solution. In addition, with the implementation of its artificial intelligence software, you will be able to make your video conferences with professional quality with its automatic focus technology by facial recognition or audio, even in motion.

Main characteristics

<p>Crystal clear image quality in 4K at 30 fps</p>	<p>Automatic framing by facial or audio recognition</p>	<p>Digital microphone up to 6 meters (supports external microphone via USB). Built-in speaker</p>	<p>USB C camera with HDMI 1.4b and 5X digital zoom</p>	<p>Compatible with ClickShare Conference by Barco and Modena by Biamp</p>
--	---	---	--	---



Cute Up 4K Pro Specifications: P/N: CUP

Camera with positioner and zoom lens

Image sensor: 1/2.5" CMOS

Effective sensor pixels: 8.29 M

Maximum output resolution: 3840x2160 4K

Horizontal viewing angle: 110°

Vertical viewing angle: 75°

Optical Zoom: /

Digital Zoom: 5X

Focusing system: auto

Shutter speed: 1/30 to 1/10000

Exposure Control: auto

Minimum illumination: 0.5 Lux @ (F1.8, AGC ON)

Noise reduction: 2D & 3D

Signal to Noise Ratio: ≥55

Vertical rotation: ±15°

Position memories: 2

Image inversion H: No

Image inversion V: No

Image freezing: No

Back light compensation: ON/OFF

Mirror function: Supported

Audio

Type of microphones: Beamforming

Pickup distance: Up to 6 meters

Sound power: 96 dB

Speaker: Integrated

Connectivity

Video output: 1xHDMI, 1xUSB-C, 1xUSB

USB

Connector: USB 3.0 and USB 2.0

Operating systems: Windows 10, Mac OS X, Linux, Android.

Multi-Stream capability: No

USB Video Class: UVC 1.1

USB Audio Class: Yes

UVC (Universal Video Class): Yes: UAC 1.0

IP Streaming

Multi-Stream capability: No

Video format: MPEG/YUY2

Video bitrate: 32 K s

HDMI

Connector: HDMI 1.4b (displays camera signal).

General

Power supply: DC 12V, 2A (Max.)

Power consumption: DC 12V, 2A (Max.)

Operating temperature and humidity: 0° C ~ 40° C



Central offices:
Av. Cerro del Águila, 3, 1B2.
S.S. de los Reyes 28703
Madrid - Spain

After-sales service:
C/Brújula, 4 Pol. Ind. PISA
Mairena del Aljarafe 41927
Seville - Spain

Dimensions: 600 x 135 x 115

Weight: 2.5 kg

Color: Black

Supplied accessories: Power supply with cable, remote control, USB 3.0 cable, table/wall mount and user manual.

Security: "Kensington" Slot.

Status indicator: Yes, LED type

Cable: USB 3.0 200 cm

Artificial Intelligence

Automatic framing through facial recognition: Yes

Automatic framing and focusing through the speaker's voice: Yes

Auto-tracking with speaker tracking: Yes

Voice-tracking with activation/deactivation via direct key with remote control: Yes

Gesture control: Yes (Through AI Cam Control - Optional)

Image adjustment and sharpening: Yes (Through AI Cam Control - Optional)

Record different camera profiles: Yes (Via AI Cam Control - Optional)

Insert PNG logos over the video signal: Yes (Through AI Cam Control - Optional)

Pixel faces: Yes (Through AI Cam Control - Optional)