

AXI-IN

Installation Series Selfpowered speakers



System data

Frequency response (-5 dB standard)	85 Hz - 19 kHz
Max. sound pressure (1 m, free field)	123 dB SPL

Loudspeaker data

Nominal impedance (Lf-Hf)	4 - 8 ohms
Power handling capacity LF (RMS/peak 10 ms)	200/400W
Power handling capacity HF (RMS/peak 5 ms)	40/80W
Nominal dispersion angle (HxV)	70°x70°
Components	2 x 5" driver with neodymium magnet 1.75" neodymium compression driver

Dimensions, weight

Dimensions (H x W x D)	173 x 384 x 261 mm 6.8 x 15.1 x 10.2"
Weight	7 kg 15 lb
Protection Rating:	IP 44
Finish	Fir-green RAL 6009® Polyurea coating
Cabinet	Baltic birch plywood
Rigging	UBRK Axi In

Amplifiers

Nominal LF Amplifier Power	300 W
Nominal HF Amplifier Power	300 W
Connectors	Input: Female XLR Loop Thru: Male XLR AC Input: powerCON AC Output: powerCON

Software control	
Signal processing	DSP: 96 kHz
AC Requirements	Universal mains 85-264Vac

Current Draw (1/8 power @ 230 V)	1.1A
----------------------------------	------