

**Features:**

- Full compliance with the EN 54-24 standard
- Easy and quick installation
- Timeless design
- Excellent sound quality for announcements and music
- Ideal for surface mounting
- 6-watt transformer adjustable in multiple stages as needed
- Thermal fuse according to BS5839-8
- Operation of two A/B speaker lines



**Technical Specifications:**

Model	ABT-W6W/AB
Rated power handling	2x6 W
Gradients – Transformers 100 V according to EN 54-24	2x6/ 3/ 1,5/ 0,75 W
Gradients – Transformers 70 V	2x3/ 1,5/ 0,75/ 0,37 W
Impedance @100 V	2x1667/ 3333/ 6667/ 13333 Ω
Nominal impedance	2x8 Ω
Effective frequency response	150-20.000 Hz
Sensitivity @ 4 m, 1 W	75 dB
Sound Pressure Level (SPL) @ 4 m, rated power handling	84 dB
SPL @ 1 m, 1 W, dB, test signal 300 Hz – 6 kHz	87 dB
SPL @ 1 m, rated power handling, test signal 300 Hz – 6 kHz	96 dB
Horizontal radiation angle 500 Hz / 1 kHz / 2 kHz / 4 kHz	225°/ 135°/ 70°/ 45°
Vertical radiation angle 500 Hz / 1 kHz / 2 kHz / 4 kHz	245°/ 190°/ 140°/ 115°
IP protection class	32
Ambient temperature min./max.	-10°C/ 55°C
Dimensions	254x196x78 mm
Net weight	1,99 kg
Color	White
Housing material	MDF

Rev.: 1.0 (240315TK)