

# elipson® | RAIN 100V

2-WAY OUTDOOR LOUDSPEAKER

Elegant design and optimal weather resistance thanks to its IP 66 waterproof standard.

Discover Elipson's RAIN 100V range of outdoor loudspeakers, the ideal solution for providing a safe and secure sound experience on your terrace. Available in two different sizes - RAIN 6 100V and RAIN 8 100V - they feature a 6" and 8" mid-bass drive units respectively.

Each loudspeaker offers outstanding sound quality, elegant design and optimal weather resistance thanks to its IP 66 waterproof standard.

Their ruggedness means you can enjoy superior sound outdoors, even in extreme weather conditions ranging from -25°C to +70°C.

The RAIN 100V loudspeakers have an ultra-rigid, UV-treated cabinet and a rustproof grille. Their modern and elegant design will blend harmoniously into your outdoor environment.

The two sizes available, the elegant design, the sturdiness and the IP 66 waterproof standard make them an ideal choice for safe patio sound, whatever the weather conditions.



RAIN 8 100V

RAIN 6 100V



### TECHNICAL

#### RAIN 6 100V

**Type**

2-way outdoor loudspeaker

**Power**

120 W RMS

**Drive units**

**Mid-woofer** : 6.5"

**Tweeter** : 1"

**Frequency response ( $\pm 3$ dB)**

80 Hz - 20 KHz

**Available powers in 100V mode**

5 W / 10 W / 20 W / 40 W

**Available powers in 70V mode**

2,5 W / 5 W / 10 W / 20 W

**Sensitivity**

89 dB / 1W / 1m

**Impedance**

8  $\Omega$

**Crossover frequency**

3000 Hz

**IP code**

IP66

**Min. temperature**

-25°C

**Max. temperature**

+70°C (25% humidity)

**Humidity resistance**

+40°C under 95%

**Treatments**

Anti-rust, anti-UV

**Dimensions**

W195 x H285 x D183 mm

**Net weight**

3,5 kg

**Dimensions packaging**

W570 x H375 x D300 mm

**Gross weight**

8,5 kg

#### RAIN 8 100V

**Type**

2-way outdoor loudspeaker

**Power**

150 W RMS

**Drive units**

**Mid-woofer** : 8"

**Tweeter** : 1"

**Frequency response ( $\pm 3$ dB)**

70 Hz - 20 KHz

**Available powers in 100V mode**

6,25 W / 12,5 W / 25 W / 50 W

**Available powers in 70V mode**

3,12 W / 6,25 W / 12,5 W / 25 W

**Sensitivity**

90 dB / 1W / 1m

**Impedance**

8  $\Omega$

**Crossover frequency**

3200 Hz

**IP code**

IP66

**Min. temperature**

-25°C

**Max. temperature**

+70°C (25% humidity)

**Humidity resistance**

+40°C under 95%

**Treatments**

Anti-rust, anti-UV

**Dimensions**

W244 x D230 x H355 mm

**Net weight**

4,6 kg

**Dimensions packaging**

W670 x H445 x D345 mm

**Gross weight**

11,5 kg

### DIMENSIONS WEIGHT

### PACKAGING

FINISHES  
-  
PRODUCTS  
CODES

 **Finish**  
White

**SKU**  
ELIRAI6WT100V

**EAN**  
3700795199213

 **Finish**  
White

**SKU**  
ELIRAI8WT100V

**EAN**  
3700795199237

 **Finish**  
Black

**SKU**  
ELIRAI6BK100V

**EAN**  
3700795199244

 **Finish**  
Black

**SKU**  
ELIRAI8BK100V

**EAN**  
3700795199220

GOOD TO KNOW

