

M50		
Specifications.	Values	Notes / Comments.
Nominal system impedance	4 ohm	(Z-min 4.9 ohm)
Frequency response	100-20Khz	(average response in room +/- 2dB)
Frequency roll off	100 Hz	(-6dB at 100 Hz near field-w all mounted)
Crossover frequency	1.8Khz	"Phase focused" (4th&2nd order)
Tweeter (shielded)	1" Dome	Coated silk dome / Neodymium magnet
Woofers (shielded)	4"	Coated glassfibre
Power handling	80 watt	Long term IEC-268-5 (cycled input 100-20Khz)
Power handling	50 watt	Rated IEC-268-5 (constant input 100-20Khz)
Recommended amp power	25-125 watt	(Recommended amp power to drive speaker)
Sensitivity	85 dB	Average SPL 2.83 Volt / 1mtr (on axis 200-10KHz)
System principle		Sealed enclosure
Connection	Terminal gold plating	Screw for 5mm cable / Banana
Accessories	Yes	Wall mount brackets/screws/gloves
Welcome card	Yes	"Included in packing"
Finish		Black or White satin
Dimensions	H x W x D	9,8 x 5,1 x 3,3 inch - 25 x 13 x 8,5cm (incl grill)
Weight		4.4 lb / 2.0 kg