

M90		
Specifications	Values	Notes / Comments
Nominal System Impedance	4 ohm	(Z-min 3.4 ohm)
Frequency Response	70-20K Hz	(average response in room +/- 2 dB)
Frequency Roll Off	70 Hz	(-10 dB 80 Hz near field wall mounted)
Crossover Frequency	600 Hz / 2.0 KHz	"Phased focused" (2nd order) Tapered
Tweeter (Shielded)	1" Dome	Coated Silk dome / Neodymium magnet
Woofer	4 x 4"	Coated Glass Fiber
Power Handling	150 watt	Long term IEC-268-5 (cycled input 80-20K Hz)
Power Handling	75 watt	Rated IEC-268-5 (constant input 80-20K Hz)
Recommended Amp Power	25-200 watt	(Recommended amp power to driver speaker)
Sensitivity	91 dB	Average SPL 2.83 volt / 1mtr (on axis 200-10K Hz)
System Principle		Sealed enclosure
Connection	Terminal Gold plating	Screw for 5mm Cable / Banana
Accessories	Yes	Wall mount Brackets/Screws/Gloves
Welcome card	Yes	"Included in packing"
Finish	Painted	Black / White Satin
Dimensions	H x W x D	31,5 x 5,1 x 3,3 inch / 80 x 13 x 8,5 cm (incl grill)
Weight	Netto	12.40 lbs / 5.62 kg
		Version 1. Jan 2021