

MP950		
Specifications.	Values	Notes / Comments.
Nominal system impedance	4 ohm	(Z-min 3.4 ohm)
Frequency response	80-20Khz	(average response in room +/- 3dB)
Frequency roll off	80 Hz	(-6db at 80 Hz near field)
Crossover frequency	1.6Khz	"Phase focused" (4th/2nd order)
Tweeter	1,1" Dome	Coated silk dome / low compression
Woofers	2 x 5.25"	Coated Glass fibre
Power handling	150 watt	Long term IEC-268-5 (cycled input 80-20Khz)
Power handling	80 watt	Rated IEC-268-5 (constant input 80-20Khz)
Recommended amp power	25-200 watt	(Recommended amp power to drive speaker)
Sensitivity	90.5 dB	Average SPL 2.83V / 1mtr (on axis 200-10KHz)
System princip		Sealed enclosure
Connection	Terminal gold plating	Screw for 6 mm cable / Banana
Accessories	Yes	Mounting screws/gloves/rubber feets
Velcome card	Yes	"Included in packing"
Finish		Black Satin / White Satin
Dimensions	H X W X D	19.6 x 6,8 x 3,9 inch / 50 x 17.5 x 10 cm
Weight	Netto	6.8 kg / 14 lbs
	Version 1. feb 2019	