

Next™ NXT-1



FEATURES

- Pixel mapping LED moving head utilizing bright 25 RGBW 10 W Osram LEDs
- Tight beam angle of 6° ensures maximum punch at long throws, with 22,780 lux at 5 meters
- Lightweight housing with ultra-fast pan/tilt movement guaranteed to keep up with your other professional moving head fixtures
- Versatile control options include Art-Net™, Kling-Net, and 3- and 5-pin DMX
- Neutrik® powerCON® and etherCON® connection for power and data linking
- Built-in web server for remote diagnostics and firmware upgrades

SPECIFICATIONS

- Control Protocol: Art-Net™, Kling-Net, DMX
- DMX Channels: 10, 13, 23, 106 or 119
- Art-Net™ Channels: 10, 13, 23, 106 or 119
- Data Connectors: 3- and 5-pin XLR, Neutrik® etherCON®
- Light Source: 25 LEDs (quad-color RGBW) 10 W, (2.9 A), 50,000 hours life expectancy
- Built-in Automated Programs: Yes
- Pan and Tilt: 540°/270°
- Pixels: 5 x 5
- Pixel Pitch: 48 mm
- Strobe Rate: 0 to 13 Hz
- Beam Angle: 6°
- Field Angle: 11°
- Illuminance (total): 22,780 lux @ 5 m
- Color Temperature (range): 2800 to 10000 K
- IP Rating: IP20, dry location
- Cable Length: 5 ft (1.5 m)
- Power Connection: Edison plug to Neutrik® powerCON®
- Power Input: Neutrik® powerCON®
- Power Output: Neutrik® powerCON®
- Power Linking: 5 units @ 120 V; 9 units @ 208 V; 10 units @ 230 V
- Input Voltage: 100 to 240 VAC, 50/60 Hz (auto-ranging)
- Power and Current: 397 W, 3.5 A @ 120 V, 60 Hz
- Power and Current: 378 W, 1.9 A @ 208 V, 60 Hz
- Power and Current: 375 W, 1.8 A @ 230 V, 50 Hz
- Weight (single unit): 30.6 lb (13.9 kg)
- Weight (road case): 101.2 lb (45.9 kg)
- Dimensions (single unit): 11.3 x 15.4 x 18.6 in (288 x 391 x 472 mm)
- Dimensions (road case): 20.4 x 31.1 x 31.7 in (520 x 790 x 807 mm)
- Accessories (optional): ArKaos MediaMaster Express™ + KN software
- Approvals: CE