

Product information

The PRA900 is a high quality microphone cable constructed using the UltraFlex™ PMC224 cable and fitted with Neutrik 6.3 mm Jack (gold contacts, black jack shell) and female XLR connectors (Silver contacts, black metal XLR housing) . The 24 AWG (0.22 mm²) thin & dense stranded bare copper conductors are surrounded by a high coverage spiral shielding. In combination with the thick and soft PVC outer jacket, this provides a flexible but solid feel. The high-purity copper, high-coverage shielding and low capacitance guarantee an optimal signal transmission. The attached shrink sleeve allows custom labeling for easy identification. It comes in different lengths of 3 meters and 5 meters, providing solutions for all applications

Highlights

- Ultraflex™ Ultra flexible jacket
- 24 AWG thin and dense stranded conductors
- 6.5 mm (Ø) outer diameter
- Oxygen free copper
- 60 mm transparent shrink sleeve
- gold contacts, black jack shell
- Silver contacts, black metal XLR housing

Components

- CableType: PMC224 - Balanced microphone cable - flex 2 x 0.22 mm² - 24 AWG - UltraFlex™
- Connector: NP2X - 1/4" professional phone plug, 2 pole.
- Connector: NC3FXX - 3 pole female cable connector with nickel housing and silver contacts.



Certification



Properties



Usage

MOBILE

RENTAL

STAGE

Wiring Diagrams



Variants

- PRA900/3 - 3 METER
- PRA900/5 - 5 METER