

### Highlights:

- Secure Safelatch™ system
- Excellent off-axis performance (up to 145°)
- Unique TwistFix™ grill design
- Borderless grill design
- Rotary switch for 16W, 32W, 64W and an 8 Ohm tapings
- Terminal block connection
- Shallow built-in depth (132 mm)
- Multi-tapping 70V / 100V line transformer

### Product information:

The CALI660 is a 2-way ceiling speaker with rear dome, constructed using a 6.5" cone driver, combined with an coaxially mounted 1" soft dome tweeter which is fitted with a phase plug for excellent off axis performance up to 145°.

The 2-way construction combination with metal rear-dome guarantees premium performance for demanding applications. A continuous power handling of 60 Watt (RMS) and maximum power handling of 120 watt is achieved, while fitted with a rotary switch for tapping of the 70/100V line transformer with tapings for 60W, 30W, 15W and an 8 Ohm bypass connection.

### Applications:


- Corporate
- Retail
- Bars & Restaurants



### Impedance:

$\Omega$  8 Ohm

## Voltage:

 70-100 Volt

## System specifications:

Peak power handling		240 W
Program power handling		120 W
RMS/AES power handling		60 W
Sound Pressure (Max. W/1m)	@ 100 V	(CALI660) 106 dB
		(CALI660I) 108 dB
	@ 8 $\Omega$	(CALI660I) 108 dB
Sensitivity (1W/1m)		(CALI660) 87 dB
		(CALI660I) 90 dB
Dispersion	Conical	145°
Frequency	Response ( $\pm$ 3 dB)	90 Hz - 20 kHz
	Range (-10 dB)	70 Hz - 20 kHz
Speaker type		2-way coaxial
Connection		Ceramic screw terminal with link through (CALI660)
		Pluggable terminal block connector with link-through (CALI660I)
Line Transformer Tappings	1	83 $\Omega$ - 100 V / Not used - 70 V / 60 W
	2	167 $\Omega$ - 100 V / 60 W - 70 V / 30 W
	3	333 $\Omega$ - 100 V / 30 W - 70 V / 15 W
	4	667 $\Omega$ - 100 V / 15 W - 70 V / 7.5 W

## Product Features:


---


Cut-out measurement	220 mm (Ø)
Dimensions	(CALI660) 242 x 120 mm (Ø x D) (CALI660I) 242 x 124 mm (Ø x D)
Built-in depth	(CALI660) 120 mm (CALI660I) 132 mm
Operating temperature	-20 °C ~ 60 °C
Construction	ABS and powder coated steel
Mounting	SafeLatch™ mounting system
Weight	3.42 kg

## Variants:

---

- CALI660I/W - White version (RAL9016)



		<b>CALI6601</b>		<b>Product description</b> SAFELATCH™ 2-WAY 6.5" CEILING SPEAKER WITH TWIST-FIX™ GRILL 60W - 70/100V & 8 OHM	
		MM [INCH]	Scale		
	1 : 2	(w x h x d) $\varnothing 242 \times 135.9 \text{ mm}$ $\varnothing 9.528 \times 5.35 \text{ ''}$	N/A	3.51 kg 7.738 lbs	