

# QuickFit™ 2-way 8" ceiling speaker with TwistFix™ grill

#### Highlights:

- TwistFix™ borderless grill design
- Excellent off axis performance
- Flat frequency response
- Consistent sound profile throughout complete family
- Exceptional intelligbillity and musical performance
- Lifetime stability and toolfree installation with unique Quickfit™ innovation

#### Product information:

Designed to offer the best value for money ratio. The CIRA series are coaxial 2-way ceiling speakers featuring exceptional intelligibility and musical performance. The TwistFix™ borderless grill design offers easy but solid assembly and a completely seamless transition from grill to ceiling. This results in a perfect blend in to its environment. The QuickFit™ installation system combined with FastCon™ connector offers lifetime stability and great installers convenience.

The CIRA8 features a 8" driver using polypropylene cone material, combined with a 1" Mylar tweeter fitted with a phase plug for excellent off axis performance. The selected materials guarantee a low distortion performance with smooth and flat frequency response. A continuous power handling of 40 Watt (RMS) and maximum power handling of 80 watt is achieved, while fitted with a multi-tapping 100V line transformer with tappings for 24W, 12W, 6W and an 8 Ohm & amp; 16 Ohm bypass connection.

### Applications:

- Corporate
- Retail
- Bars & Restaurants



## System specifications:

Peak power handling		160 W
Program power handling		80 W
RMS/AES power handling		40 W
Sound Pressure (Max. W/1m)	@ 100 V	105 dB
Sensitivity (1W/1m)		89 dB
Frequency	Response (± 3 dB)	40 Hz - 20 kHz
Speaker type		2-way coaxial
Impedance		8 Ω (CIRA824)
		16 Ω (CIRA840D)
Frequency	Range (-10 dB)	33 Hz - 20 kHz
Dispersion	Conical	140°
Connectors		Multi-tap Fast-con™ connections
Drivers	HF	1″
	LF	8″
Line Transformer Tappings	1	24 W - 417 Ω (CIRA824)
	2	12 W - 833 Ω (CIRA824)
	3	6 W - 1667 Ω (CIRA824)

### Product Features:

Cut-out measurement	243 mm (Ø)	
Dimensions	270 x 82 mm (Ø x D)	
Weight	1.65 kg (CIRA840D)	
	1.75 kg (CIRA824)	
Operating temperature	-20 °C ~ 60 °C	
Construction	ABS	
Front finish	Twist-Fix™ borderless finely perforated steel grill	
Built-in depth	82 mm	
Mounting	QuickFit™ mounting system	
Colours	White (RAL9003) (CIRA824/W & CIRA840D/W)	

#### Variants:

- CIRA840DI/W White version, 16  $\Omega$  (RAL9016)
- CIRA824I/W White version,  $8\Omega \& 24$  Watt @ 100V (RAL9016)
- CIRA840D/W White version, 16  $\Omega$

Polars:





