

DW5066 Digital all-in-one wall panel

Highlights:

- · unbalanced stereo line input
- 2.5" LCD display with intuitive user interface
- · Terminal block connection

The DW5066 is an all-in-one wall panel controller for multi-zone digital audio matrix systems and multi-media digital audio mixers. It offers various control functions such as audio source selection whereby the routing can be changed or specific mixing presets ('scenes' - only for M2) can be triggered. The control shall be done using the versatile rotatable push dial whereby other settings such as volume, tone control, phantom power, muting, ... also can be made. A local line and microphone level input allows the connection of additional input units to be patched with the matrix / mixer while one of them can also be converted to a local line output. The additional inputs allow connection of a CD-player, MP3 player or any other audio source as local input while a microphone can be connected for making announcements. Both line and microphone audio input can be mixed locally using two pushlock potentiometers and 15V phantom power can be enabled to the microphone input for powering condenser microphones. The audio output function can be very useful in applications where a local audio output is required carrying the same audio signal as one of the direct outputs. This can be very useful for monitoring, recording or other system expansion purposes. A 2.5" graphical LCD display ensures a user-friendly experience for controlling the system and the audio connections are performed using XLR (microphone) and stereo RCA (line) connectors

Applications:

- · Bars, restaurants
- Retail
- Hotels
- Corporate spaces
- Residential



System specifications:

Control			RS-485
Digital audio			S/PDIF
Inputs	Balanced Stereo	Туре	1 x Stereo Balanced Line
		Connector	RCA
	Balanced Microphone	Туре	1 x Balanced Microphone
		Connector	XLR female
Phantom Power			15 V DC (software enabling)
Cabling			UTP CAT 6 (Up to 300 meter)
Display	Туре		2.5" Graphical Full colour
Connectors			8-pin Euro Terminal Block

Product Features:

Dimensions			153 x 94 x 45 mm (W x H x D)
Built-in depth			37 mm
Weight			0.210 kg
Construction			ABS
Colours			Black (RAL9005) (DW5066/B)
			White (RAL9010) (DW5066/W)
Accessories	Optional	Flush mount Installation boxes	WB5065/FS: Concrete & Brick walls
			WB5065/FG: Wooden & Gypsum walls
		Surface mount Installation boxes	WB5065/SW: White version
			WB5065/SB: Black version
	Repeater (>300 m)		CP43ARP: bTicino version (/B & /W)
			CP45ARP: 45x45mm version (/B & /W)

Variants:

- DW5066/B Black version
- DW5066/W White version

