



Description:

Our USB3.0 (data only) Type-A male to Type-A female Active Optic Cable is suited for critical and versatile installations where distance is required. This supports USB3.0 superspeed device connectivity with up to 10Gbps of data transfer over a light weight, flexible and ultra-small bend radius (40mm) in a hybrid cable.

Key Features:

- Supports USB3.0 - compatible and incompatible versions
- Supports USB2.0 and USB1.1 devices - compatible version only
- Supports all USB3.0 device types: control, interrupt, bulk and isochronous at up to 10Gbps
- Operates with USB3.0 superspeed host controllers
- Support for Windows, Linux and iOS operating systems
- Plug and Play - no drivers or downloads required
- All cables are of CMP (Plenum-rated) jacket

Technical Specifications:

| | |
|-------------------------------|---|
| Cable Diameter: | 4.5mm |
| Operating Temperature: | 32°F to 122°F (0°C to 50°C) |
| Storage Temperature: | -4°F to 140°F (-20°C to 60°C) |
| Operating Humidity: | 10-80% non condensing |
| Available in Lengths: | 15m and 30m |
| Package Contents: | 1x MS-USBAA Cable - 15m or 30m |
| Compatibility: | |
| MS-USBMF-15-BC | USB 3.0 AM-AF AOC, (Compatible Version) |
| MS-USBMF-30 | USB 3.0 AM-AF AOC, (Incompatible Version) |