

<b>S150</b>		
<b>Specifications.</b>	<b>Values</b>	<b>Notes / Comments.</b>
Nominal system impedance	4 ohm	(Z-min 3.4 ohm)
Frequency response	75-20Khz	(average response in room +/- 3dB)
Frequency roll off	80 Hz	(-6db 80 Hz near field)
Crossover frequency	1.6Khz	"Phase focused" (4th/2nd order)
Tweeter	3 x 1,1" Dome	Coated silk dome / Low compression
Woofers	2 x 5.25"	Coated Glassfibre
Power handling	180 watt	Long term IEC-268-5 (cycled input 77-20Khz)
Power handling	90	Rated IEC-268-5 (constant input 77-20Khz)
Recommended amp power	25-400 watt	Recommended amp power min / max
Sensitivity	91dB	Average SPL 2.83 volt / 1mtr (on axis 200-10KHz)
Max continued SPL	110 dB	Sine wave 100-8000 Hz / THD <10%
Max SPL Peak	114 dB	Sine wave 100-8000 Hz / THD <10%
System principle		Sealed enclosure
Connection	Terminal gold plating	Screw for 6 mm cable / Banana
Accessories	Yes	"Mounting screws & gloves"
Welcome card	Yes	"Included in packing"
Certification THX	Yes	THX Ultra Certified
Finish	Paint	Black Satin
Dimensions	H x W x D	12.5x10.5x12.5 inch - 31.8x26.8x31.8cm
Weight	Netto	24 lb / 11 kg
	Version 1. Feb 2019	